Electric Power Steering Apparatus

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to an electric power steering apparatus so configured as to transmit a driving force produced by an electric motor to a steering mechanism as a steering assist force.

Description of Related Art

Electric power steering apparatuses so configured as to perform steering assist by mechanically transmitting a driving force produced by an electric motor to a steering mechanism by a gear mechanism (a speed reduction mechanism) or a direct drive system have been conventionally employed.

In such electric power steering apparatuses, assist characteristics for determining the relationship between a steering torque applied to a steering wheel and an assist torque target value given to the steering mechanism from the electric motor have been previously determined, and are stored in a memory as an assist map. The assist torque target value corresponding to the steering

torque is read out of the assist map, and the electric motor is driven and controlled on the basis of the read assist torque target value.

The assist characteristics are determined
5 such that the larger the steering torque is, the larger the assist torque target value becomes, as shown in Fig. 7. A positive value is assigned to the steering torque with respect to a rightward steering direction, while a negative value is
10 assigned to the steering torque with respect to a leftward steering direction, for example. The assist characteristics are so determined that a positive value of the assist torque target value corresponds to the steering torque taking the
15 positive value, and a negative value of the assist torque target value corresponds to the steering torque taking the negative value.

When the assist torque target value is a positive value, such a steering assist force as
20 to steer a steerable wheel rightward is exerted on the steering mechanism. Conversely, when the assist torque target value is a negative value, such a steering assist force as to steer a steerable wheel leftward is exerted on the
25 steering mechanism. When the steering torque

takes a value in a dead zone in the vicinity of zero, the assist torque target value is made zero.

In such electric power steering apparatuses to which such assist characteristics are applied, when return stroke steering for rotating a steering wheel toward a steering angle midpoint is done, such a steering feeling (a so-called spring feeling) that the steering wheel is returned to the steering angle midpoint strongly than a driver intends is produced. That is, when return stroke steering is done, a steering torque is reduced and correspondingly, an assist force is reduced. Accordingly, the steering wheel is returned to the steering angle midpoint strongly by an inverted input from the steerable wheel.

This problem can be solved by increasing the slope of an assist characteristics curve such that a larger assist torque target value is set with respect to the steering torque. In this case, however, a responsive feeling at the time of forward stroke steering is degraded.

SUMMARY OF THE INVENTION

Therefore, the applicant of the present invention has proposed to correct reference assist characteristics on the basis of a steering speed

in Japanese Patent Application NO. 2002-160061 previously filed, to provide an electric power steering apparatus so configured as to perform steering assist in accordance with corrected

5 assist characteristics obtained by the correction.

In the electric power steering apparatus according to the prior application, reference assist characteristics are shifted along the axis

10 of coordinates of a steering torque depending on a steering speed, thereby obtaining corrected assist characteristics. More specifically, the shifting direction and the shifting amount of the reference assist characteristics are variably set

15 depending on the direction of the steering speed (equal to a steering direction) and the magnitude thereof, for example. For example, the corrected assist characteristics are found by shifting the reference assist characteristics in the positive

20 direction on the axis of the steering torque when the steering speed takes a positive value, while shifting the reference assist characteristics in the negative direction on the axis of the steering torque when the steering speed takes a negative

25 value as well as determining the shifting amount

such that the shifting amount increases monotonously (for example, linearly) depending on the absolute value of the steering speed.

A motor driving target value is set in accordance with the corrected assist characteristics thus obtained, thereby making it possible to set assist characteristics which differ at the time of forward stroke steering and return stroke steering. Consequently, a sufficient responsive feeling can be obtained at the time of forward stroke steering, and a sufficient steering assist force is transmitted to a steering mechanism at the time of return stroke steering, thereby making it possible to cancel such an undesirable steering feeling (spring feeling) that a steering wheel is returned to a neutral position more strongly than a driver intends.

In such a configuration, however, the driver's steering effort on the steering wheel differs depending on the steering speed. Therefore, tuning for optimizing the reference assist characteristics for each vehicle type is difficult.

An object of the present invention is to

provide an electric power steering apparatus in which a good steering feeling can be realized, and reference assist characteristics are easy to tune.

An electronic power steering apparatus according to the present invention is an apparatus for performing steering assist by transmitting a driving force produced by an electronic motor to a steering mechanism. The apparatus comprises an operation amount sensor for sensing an operation amount of an operation member for steering a motor vehicle; a reference assist characteristics setting section for setting reference assist characteristics which are reference characteristics of a motor driving target value corresponding to the operation amount sensed by the operation amount sensor; a motor driving target value setting section for setting the motor driving target value corresponding to the operation amount sensed by the operation amount sensor in accordance with corrected assist characteristics obtained by shifting the reference assist characteristics set by the reference assist characteristics setting section along the axis of coordinates of the operation amount; and a motor driving section for driving

the electric motor on the basis of the motor
driving target value set by the motor driving
target value setting section. The apparatus
further comprises a shifting amount setting
5 section for setting, when forward stroke steering
for operating the operation member in a direction
away from a steering angle midpoint is done, the
shifting amount of the corrected assist
characteristics with respect to the reference
10 assist characteristics to zero, while setting,
when return stroke steering for operating the
operation member toward the steering angle
midpoint is done, the shifting amount of the
corrected assist characteristics with respect to
15 the reference assist characteristics to a value
at which corrected assist characteristics is
obtained in which the absolute value of the motor
driving target value corresponding to the
operation amount sensed by the operation amount
20 sensor is increased.

　　　According to the present invention, the
corrected assist characteristics obtained by
correcting the reference assist characteristics
set by the reference assist characteristics
25 setting section are applied to the operation

amount sensed by the operation amount sensor. That is, the motor driving target value is set in accordance with the corrected assist characteristics.

5   Although the reference assist characteristics are corrected by shifting the reference assist characteristics along the axis of coordinates of the operation amount, the shifting amount is determined such that the

10 shifting amount is made zero at the time of forward stroke steering (at the time of steering in the direction away from the steering angle midpoint), and that the shifting amount is made a value corresponding to the corrected assist

15 characteristics in which the absolute value of the motor driving target value is made larger than that in the case of the reference assist characteristics at the time of return stroke steering (at the time of steering in the direction

20 nearer to the steering angle midpoint).

More specifically, there is provided a steering speed sensor, for example, for sensing a steering speed by the operation member, and the shifting direction and the shifting amount of the

25 reference assist characteristics are variably set

depending on the direction of the steering speed (equal to a steering direction) sensed by the steering speed sensor and the magnitude thereof. For example, it is assumed that a steering torque

5 sensed by a steering torque sensor which is an example of the operation amount sensor takes a positive value with respect to a rightward steering direction, while taking a negative value with respect to a leftward steering direction. In

10 the reference assist characteristics, it is assumed that a positive value of the motor driving target value is assigned to the steering torque value taking the positive value, while a negative value of the motor driving target value is assigned

15 to the steering torque value taking the negative value. Further, the steering speed takes a positive value with respect to the rightward steering direction, while taking a negative value with respect to the leftward steering direction.

20　　　In this case, in a case where the steering torque is not less than zero, for example, the shifting amount may be made zero when the steering speed takes a positive value of not less than a first predetermined value (at the time of forward

25 stroke steering), while being determined

depending on the steering speed when the steering speed takes a value of less than the first predetermined value. At this time, the reference assist characteristics may not be shifted in the

5 positive direction on the axis of coordinates of the steering torque, but may be exclusively shifted in the negative direction on the axis of coordinates of the steering torque. That is, the shifting amount may be determined such that its

10 value in a case where the steering speed takes the first predetermined value is zero and such that it decreases monotonously (for example, in a stepped shape or linearly), as the steering speed decreases, to a negative lower-limit value with

15 respect to the steering speed which is less than the first predetermined value. In the reference assist characteristics, therefore, a portion in a range of the steering torque taking the positive value is shifted toward the origin, so that the

20 steering assist force increases, thereby making it possible to improve a spring feeling at the time of return stroke steering. The above-mentioned predetermined value may be determined to be not less than zero. If the first predetermined value

25 is set to a positive value, however, the steering

assist force can be increased in a steering hold-on state where the steering speed becomes approximately zero, thereby making it possible to reduce a steering burden on a driver in the steering hold-on state. Further, in a return stroke steering state where the steering speed takes a negative value, the shifting amount may be variably set depending on the steering speed, or may be fixed to the negative lower-limit value irrespective of the steering speed.

In a case where the steering torque takes a negative value, the shifting amount may be made zero when the steering speed takes a negative value of not more than a second predetermined value, while being determined depending on the steering speed when the steering speed takes a value exceeding the second predetermined value. At this time, the reference assist characteristics may not be shifted in the negative direction on the axis of coordinates of the steering torque, but may be exclusively shifted in the positive direction on the axis of coordinates of the steering torque. That is, the shifting amount may be determined such that its value in a case where the steering speed takes a second predetermined value is zero and such

that it increases monotonously (for example, in a stepped shape or linearly), as the steering speed increases, to a positive upper-limit value with respect to the steering speed exceeding the second predetermined value. In the reference assist characteristics, therefore, a portion in a range of the steering torque taking the negative value is shifted toward the origin, so that the steering assist force increases, thereby making it possible to improve a spring feeling at the time of return stroke steering. The above-mentioned second predetermined value may be determined to be not more than zero. If the second predetermined value is set to a negative value, the steering assist force can be increased in a steering hold-on state where the steering speed becomes approximately zero, thereby making it possible to reduce a steering burden on a driver in the steering hold-on state. In a return stroke steering state where the steering speed takes a positive value, the shifting amount may be variably set depending on the steering speed, or may be fixed to a positive upper-limit value irrespective of the steering speed.

The motor driving target value is set in

accordance with the corrected assist

characteristics thus obtained, so that different

assist characteristics can be set at the time of

forward stroke steering and at the time of return

5 stroke steering. Consequently, a sufficient

responsive feeling can be obtained at the time of

forward stroke steering, and a sufficient steering

assist force is transmitted to the steering

mechanism at the time of return stroke steering,

10 thereby making it possible to cancel such an

undesirable steering feeling (spring feeling)

that a steering wheel is returned to a neutral

position more strongly than the driver intends.

Moreover, at the time of forward stroke steering,

15 a reference assist map is used as it is. Therefore,

a steering burden does not vary depending on the

steering speed, so that the reference assist map

is easy to tune.

The electric power steering apparatus may

20 further comprise a vehicle speed sensor for

sensing the vehicle speed of the motor vehicle

equipped with the electric power steering

apparatus, and a vehicle speed adaptive shifting

amount setting section for variably setting the

25 shifting amount of the corrected assist

characteristics with respect to the reference

assist characteristics depending on the vehicle

speed sensed by the vehicle speed sensor.

In this configuration, the shifting amount of

5 the reference assist characteristics can be

variably set depending on the vehicle speed.

Accordingly, this can cope with a case where it

is not so necessary to correct the assist

characteristics, for example, a steering

10 operation at the time of a stop or at the time of

low-speed traveling.

The electric power steering apparatus may

further comprise a steering torque sensor for

sensing the steering torque applied to the

15 operation member (which may be shared with the

above-mentioned operation amount sensor), and a

steering torque adaptive shifting amount setting

section for variably setting the shifting amount

of the corrected assist characteristics with

20 respect to the reference assist characteristics

depending on the steering torque sensed by the

steering torque sensor.

By this configuration, when the steering

torque takes a small value in the vicinity of zero,

25 for example, the shifting amount can be restrained

or reduced to zero. Consequently, it is possible to restrict steering assist in a very small steering torque range where no steering assist is required.

5   The foregoing and other objects, features, aspects and advantages of the present invention will become more apparent from the following detailed description of the present invention when taken in conjunction with the accompanying
10 drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

        Fig. 1 is a block diagram showing the electrical configuration of an electric power steering apparatus according to an embodiment of
15 the present invention;

        Fig. 2 is a diagram for explaining reference assist characteristics and corrected assist characteristics obtained by shifting the reference assist characteristics along the axis
20 of coordinates of a steering torque;

        Figs. 3 (a) and 3 (b) are diagrams showing the relationship of a reference shifting amount to a steering angular velocity;

        Fig. 4 is a diagram for explaining variable
25 setting of a shifting amount with respect to a

vehicle speed;

Fig. 5 is a diagram for explaining variable setting of a shifting amount with respect to a steering torque;

5   Fig. 6 is a flow chart for explaining processing related to driving control of an electric motor by a microprocessor; and

Fig. 7 is a diagram showing an example of assist characteristics.

10 DESCRIPTION OF THE PREFERRED EMBODIMENTS

Fig. 1 is a block diagram showing the electrical configuration of an electric power steering apparatus according to an embodiment of the present invention. A steering torque applied

15 to a steering wheel 1 serving as an operation member is mechanically transmitted to a steering mechanism 3 including a rack shaft through a steering shaft 2. A steering assist force is mechanically transmitted to the steering

20 mechanism 3 from an electric motor M through a driving force transmitting mechanism such as a gear mechanism (a speed reduction mechanism) or a direct drive system.

The steering shaft 2 is divided into an input

25 shaft 2A coupled to the steering wheel 1 and an

output shaft 2B coupled to the steering mechanism 3. The input shaft 2A and the output shaft 2B are connected to each other by a torsion bar 4. The torsion bar 4 causes distortion depending on the steering torque. The direction and the amount of the distortion are sensed by a torque sensor 5.

The torque sensor 5 is of a magnetic type, for example, for sensing a magnetoresistance which varies depending on the change in the positional relationship in the direction of rotation between the input shaft 2A and the output shaft 2B. An output signal of the torque sensor 5 is inputted to a controller 10 (ECU : Electronic Control Unit).

An output signal of a vehicle speed sensor 6 for sensing the traveling speed of a motor vehicle equipped with the electric power steering apparatus and an output signal of a steering angle sensor 7 for sensing the steering angle of the steering wheel 1 (e.g., a rotation angle of the input shaft 2A) are further inputted to the controller 10.

The controller 10 determines an assist torque target value to be given to the steering mechanism 3 from the electric motor M depending on a steering torque sensed by the torque sensor 5, a vehicle

speed sensed by the vehicle speed sensor 6, and

an output of the steering angle sensor 7, in order

to drive and control the electric motor M such that

a steering assist force corresponding to the

5 steering torque and the like is applied to the

steering mechanism 3.

The controller 10 has a microprocessor 20 and

a motor driver 30 for driving the electric motor

M on the basis of a control signal from the

10 microprocessor 20.

The microprocessor 20 comprises an assist

torque target value setting section 21 which is

a functional processing unit realized by executing

program-based processing, and an assist

15 characteristics storing section 22 composed of a

storage area of a memory in the microprocessor 20.

The assist characteristics storing section 22

stores a plurality of reference assist maps

respectively corresponding to a plurality of

20 reference assist characteristics previously

determined with respect to a plurality of vehicle

speed areas. The reference assist characteristics

are obtained by determining reference

characteristics of an assist torque target value

25 corresponding to a steering torque, and the

reference value of the assist torque target value
is stored in the assist characteristics storing
section 22 in the form of an assist map (a table)
in correspondence with the values of a plurality

5 of steering torques.

The microprocessor 20 further comprises a
steering angular velocity computing section 23 for
computing a steering angular velocity on the basis
of the output signal of the steering angle sensor

10 7, and a shifting amount computing section 24 for
computing a shifting amount in a case where the
reference assist characteristics are shifted
along the axis of coordinates of the steering
torque to obtain virtual corrected assist

15 characteristics. The shifting amount computing
section 24 computes a shifting amount for
obtaining virtual corrected assist
characteristics obtained by shifting the
reference assist characteristics along the axis

20 of coordinates of the steering torque on the basis
of a steering angular velocity ω computed by the
steering angular velocity computing section 23,
a vehicle speed V sensed by the vehicle speed
sensor 6, and a steering torque Th sensed by the

25 torque sensor 5.

The assist torque target value setting
section 21 reads out an assist torque target value
Ta corresponding to the corrected assist
characteristics from the assist characteristics

5 storing section 22 on the basis of the steering
torque Th sensed by the torque sensor 5, the
vehicle speed V sensed by the vehicle speed sensor
6, and a shifting amount ΔTh computed by the
shifting amount computing section 24 (its sign

10 represents a shifting direction, and its absolute
value represents a shifting length). The motor
driver 30 supplies a necessary and sufficient
driving electric current to the electric motor M
on the basis of the read assist torque target value

15 Ta.

Fig. 2 is a diagram for explaining reference
assist characteristics corresponding to the
reference assist map stored in the assist
characteristics storing section 22 and corrected

20 assist characteristics obtained by shifting the
reference assist characteristics along the axis
of coordinates of the steering torque.

The steering torque Th sensed by the torque
sensor 5 takes a positive value when a torque for

25 rightward steering is applied to the steering

wheel 1, while taking a negative value when a torque for leftward steering is applied to the steering wheel 1. The reference assist characteristics are indicated by a curve L0 in Fig.

5 2. The reference assist characteristics are so determined that a positive value of the assist torque target value Ta corresponds to the steering torque Th taking the positive value, and a negative value of the assist torque target value Ta

10 corresponds to the steering torque Th taking the negative value. Although as described in the foregoing, the assist characteristics storing section 22 stores a plurality of reference assist maps corresponding to a plurality of vehicle speed

15 areas, one reference assist characteristics applied in a certain vehicle speed area are illustrated in Fig. 2 for simplicity of illustration.

In the reference assist characteristics

20 indicated by the curve L0, the assist torque target value Ta is set to zero irrespective of the value of the steering torque Th in the vicinity of Th = 0. Such a range of the steering torque is a dead zone NS.

25 In the present embodiment, the assist torque

target value Ta is set on the basis of virtual

corrected assist characteristics (e.g.,

characteristics indicated by curves L11 and L12)

obtained by shifting the reference assist

5 characteristics along the axis of coordinates of

the steering torque Th (in the positive direction

or the negative direction) by the shifting amount

ΔTh computed by the shifting amount computing

section 24 on the basis of the steering angular

10 velocity ω computed by the steering angular

velocity computing section 23, the vehicle speed

V, and the steering torque Th.

However, the reference assist

characteristics are shifted only in the negative

15 direction on the axis of coordinates of the

steering torque Th in situations where the

steering torque Th is not less than zero (see the

curve L11), while being shifted only in the

positive direction on the axis of coordinates of

20 the steering torque Th in situations where the

steering torque Th takes a negative value (see the

curve L12), as described below.

Figs 3 (a) and 3 (b) are diagrams for

explaining the function of the shifting amount

25 computing section 24, where the relationship of

a reference shifting amount ΔTh_B to a steering angular velocity ω. The shifting amount computing section 24 multiples the reference shifting amount ΔTh_B by a vehicle speed gain G_V and a torque gain

5   G_T, described later, to find a shifting amount ΔTh $(= G_V \times G_T \times \Delta Th_B)$.

The shifting amount computing section 24 has a memory storing a table corresponding to a curve (a polygonal line in this example) of the

10 characteristics shown in Figs. 3 (a) and 3 (b), for example. The shifting amount computing section 24 determines the reference shifting amount ΔTh_B in accordance with a table of characteristics shown in Fig. 3 (a) when the

15 steering torque Th satisfies Th $\geqq$ 0, while determining the reference shifting amount ΔTh_B in accordance with a table of characteristics shown in Fig. 3 (b) when the steering torque Th satisfies Th < 0.

20   In the table of the characteristics shown in Fig. 3 (a) applied when Th $\geqq$ 0, the reference shifting amount ΔTh_B which is zero or negative is set in a range where the steering angle velocity ω is not more than a first predetermined value $\omega 1$

25 (>0). More specifically, in a range where the

steering angular velocity ω is not more the first predetermined value ω1, the reference shifting amount ΔTh_B is so set as to decrease monotonously (linearly in the example shown in Fig. 3 (a)) using a lower-limit value β (where β < 0) as a lower limit as the steering angular velocity ω decreases. Contrary to this, in a range where the steering angular velocity ω exceeds the first predetermined value ω1, the reference shifting amount ΔTh_B satisfies $\Delta Th_B = 0$ without depending on the steering angular velocity ω.

On the other hand, in the table of the characteristics shown in Fig. 3 (b) applied when Th < 0, the reference shifting amount ΔTh_B which is zero or positive is set in a range where the steering angular velocity ω is not less than a second predetermined value ω2 (where ω2 < 0. For example, |ω2| = ω1.) In the foregoing range, the reference shifting amount ΔTh_B which is zero or positive is set. More specifically, in a range where the steering angular velocity ω is not less than the second predetermined value ω2, the reference shifting amount ΔTh_B is so set as to increase monotonously (linearly in the example shown in Fig. 3 (b)) using an upper-limit value

α (where $\alpha < 0$. For example, $\alpha = |\beta|$.) as an upper

limit as the steering angular velocity ω

increases. Contrary to this, in a range where the

steering angular velocity ω is less than the second

5 predetermined value $\omega 2$, the reference shifting

amount ΔTh_B satisfies $\Delta Th_B = 0$ without depending

on the steering angular velocity ω.

At the time of forward stroke steering in

which the direction of the steering torque Th and

10 the direction of the steering angular velocity ω

coincide with each other (at the time of steering

in a direction away from a steering angle

midpoint), the reference shifting amount ΔTh_B

becomes zero. On the other hand, at the time of

15 return stroke steering in which the direction of

the steering torque Th and the direction of the

steering angular velocity ω do not coincide with

each other (at the time of steering in a direction

nearer to the steering angle midpoint), the

20 reference shifting amount ΔTh_B is so determined

that the reference assist characteristics are

shifted in a direction nearer to the origin along

the axis of coordinates of the steering torque.

Further, when the steering angular velocity ω

25 takes a value in the vicinity of zero ($\omega 2 < \omega < \omega 1$),

the reference shifting amount ΔTh_B is so
determined that the reference assist
characteristics are shifted in the direction
nearer to the origin along the axis of coordinates
5 of the steering torque.

In such a manner, at the time of forward stroke
steering, the reference assist characteristics
are not shifted. Therefore, a steering burden does
not vary depending on the steering angular
10 velocity, the reference assist characteristics
can be easily tuned, and a sufficient responsive
feeling can be given to a driver. On the other
hand, at the time of return stroke steering and
at the time of hold-on steering, a spring feeling
15 at the time of return stroke steering can be
canceled by shifting the reference assist
characteristics toward the origin, and a good
steering feeling can be realized by reducing a
steering burden at the time of hold-on steering.
20   Fig. 4 is a diagram for explaining variable
setting of a shifting amount ΔTh corresponding to
a vehicle speed V, and Fig. 5 is a diagram for
explaining variable setting of a shifting amount
ΔTh corresponding to a steering torque Th. The
25 shifting amount computing section 24 finds a

reference shifting amount ΔTh_B in accordance with the characteristics shown in Fig. 3, and further multiples the reference shifting amount ΔTh_B by a vehicle speed gain G_V determined in accordance with characteristics shown in Fig. 4 and a torque gain G_T determined in accordance with characteristics shown in Fig. 5, to find a shifting amount $\Delta Th (= \Delta Th_B \times G_V \times G_T)$. The assist torque target value setting section 21 retrieves the reference assist map stored in the assist characteristics storing section 22 using the shifting amount ΔTh, thereby reading out an assist torque target value Ta conforming to corrected assist characteristics which are virtually determined depending on a steering angular velocity ω, a vehicle speed V, and a steering torque Th.

The vehicle speed gain G_V is so determined as to increase monotonously (linearly in this example) using a predetermined upper-limit value ("1" in the example shown in Fig. 4) as an upper limit as the vehicle speed V increases when the vehicle speed V is in a range from zero to a predetermined speed.

This can also cope with a case where the assist characteristics need not be so corrected, for

example, a steering operation at the time of a stop or at the time of low-speed traveling.

On the other hand, the torque gain G_T uses a region in the vicinity of the steering torque Th = 0 as a dead zone, and is so set as to increase monotonously (linearly in this example) using a predetermined upper-limit value ("1" in this example) as an upper limit as the absolute value of the steering torque Th increases outside the dead zone. Consequently, steering assist in a range where no steering assist is required in the vicinity of the steering torque Th = 0 is restricted.

On the basis of the shifting amount ΔTh determined in the foregoing manner, the assist torque target value Ta is determined in accordance with virtual corrected assist characteristics obtained by shifting the reference assist characteristics by the shifting amount ΔTh along the axis of coordinates of the steering torque.

More specifically, when it is assumed that the reference assist characteristics are represented by Ta = f (Th) using a function f, a value obtained by subtracting the shifting amount ΔTh from the steering torque Th sensed by the torque sensor 5

is used as a steering torque value for assist map

retrieval Th^* (that is, $Th^* = Th - \Delta Th$), and the

reference assist map stored in the assist

characteristics storing section 22 may be

5   retrieved using the steering torque value for

retrieval Th^*. Consequently, the assist torque

target value Ta $(= f(Th^*))$ can be determined in

accordance with the virtual corrected assist

characteristics.

10   Fig. 6 is a flow chart for explaining the

function of the microprocessor 20. The

microprocessor 20 reads a vehicle speed V sensed

by the vehicle speed sensor 6 and a steering torque

Th sensed by the torque sensor 5 (steps S1 and S2).

15 Further, an output signal of the steering angle

sensor 7 is read, thereby finding a steering

angular velocity ω by the steering angular

velocity computing section 23 (step 3). The

shifting amount computing section 24 reads out a

20 reference shifting amount ΔTh_B corresponding to

the found steering angular velocity ω on the basis

of the steering angular velocity ω (step S4).

Further, the shifting amount computing section 24

finds a vehicle speed gain G_V on the basis of the

25 vehicle speed V sensed by the vehicle speed sensor

6 (step S5). Further, the shifting amount computing section 24 finds a torque gain G_T on the basis of the steering torque Th sensed by the torque sensor 5 (step S6). The shifting amount

5 ΔTh is computed by multiplying the reference shifting amount ΔTh$_B$ by the vehicle speed gain G_v and the torque gain G_T thus found (step S7).

The found shifting amount ΔTh is given to the assist torque target value setting section 21. The

10 assist torque target value setting section 21 finds the steering torque value for retrieval Th* as Th*$\leftarrow$Th$-\Delta$Th, and retrieves the reference assist map stored in the assist characteristics storing section 22 on the basis of the steering torque

15 value for retrieval Th* (step S8).

In such a manner, an assist torque value Ta conforming to virtual corrected assist characteristics obtained by shifting reference assist characteristics along the axis of

20 coordinates of the steering torque by the shifting amount ΔTh is read out of the assist characteristic storing section 22. The motor driver 30 is controlled on the basis of the read assist characteristic target value Ta, and the motor M

25 produces a driving force corresponding thereto,

to supply the produced driving force to the steering mechanism 3.

Although description has been made of one embodiment of the present invention, the present invention can be also embodied in another embodiment. Although in the above-mentioned embodiment, the vehicle speed V and the steering torque Th are considered with respect to the shifting amount ΔTh of the assist characteristics, variable setting of a shifting amount dependent on the vehicle speed V and the steering torque Th is not necessarily required. That is, the reference shifting amount ΔTh_B in the above-mentioned embodiment may be used as it is as the shifting amount ΔTh, only the vehicle speed gain G_V may be multiplied by the reference shifting amount ΔTh_B without using the torque gain G_T to find a shifting amount ΔTh, and only the torque gain G_T may be multiplied by the reference shifting amount ΔTh_B without using the vehicle speed gain G_V to find a shifting amount ΔTh.

Although in the above-mentioned embodiment, the assist map corresponding to the reference assist characteristics is stored in the assist characteristics storing section 22, to read out

the assist torque target value Ta from the assist

map, the assist torque target value Ta

corresponding to the steering torque value for

retrieval Th* may be determined by a functional

5 operation.

The same is true for the shifting amount

computing section 24. The characteristics of the

reference shifting amount ΔTh_B corresponding to

the steering angular velocity ω may be previously

10 stored in the memory, or the reference shifting

amount ΔTh_B corresponding to the steering angular

velocity ω may be found by a functional operation.

The same is true for operations of the vehicle

speed gain G_V corresponding to the vehicle speed

15 V and the torque gain G_T corresponding to the

steering torque Th.

Although in the above-mentioned embodiment,

description has been made using the assist torque

target value as a motor driving target value and

20 using the characteristics of the assist torque

target value corresponding to the steering torque

as assist characteristics, the present invention

is not limited to the same. For example, a motor

current target value or a motor voltage target

25 value may be taken as a motor driving target value,

and the relationship between the steering torque and the motor current target value or the motor voltage target value may be taken as assist characteristics.

Furthermore, although in the above-mentioned embodiment, the steering angle sensed by the steering angle sensor 7 is subjected to time differential to compute the steering angular velocity, a counter- electromotive force produced between terminals of the electric motor M may be found on the basis of an output of a motor current detection circuit for finding a motor current flowing through the electric motor M and an output of a between-terminals voltage detection circuit for detecting a voltage between the terminals of the electric motor M without using a steering angle sensor, in order to estimate a steering angular velocity corresponding thereto.

Although the present invention has been described and illustrated in detail, it is clearly understood that the same is by way of illustration and example only and is not to be taken by way of limitation, the spirit and scope of the present invention being limited only by the terms of the appended claims.

The present application corresponds to Japanese application NO. 2003-51539 filed with the Japanese Patent Office on February 27, 2003, the disclosure of which is hereinto incorporated by reference.